

# Technical data

Collection	Si-Bel	
Top finish	Mat	
Size	15X15 & 60X60	
Product type	Dry pressed ceramic, single fired, procelain tiles	
Thickness	8 mm & 8,8mm	
Intended use	For interior walls & floors	
Slip resistance	DIN-51130	R10
Dimensional features	UNE-EN-ISO-10545-2	Conforms to the requisites
Water absorption	UNE-EN-ISO-10545-3	E>0.5%
Bending strenght Modulus of rupture Breaking strenght	UNE-EN-ISO-10545-4	>35Nw/mm <sup>2</sup> >1300Nw
Resistance to surface abrasion	UNE-EN-ISO-10545-7	Class 4
Linear thermal expansion	UNE-EN-ISO-10545-8	<9*10 <sup>-6</sup> /°C
Thermal shock restistance	UNE-EN-ISO-10545-9	Stands the test
Cracking resistance	UNE-EN-ISO-10545-11	Stands the test
Frost resistance	UNE-EN-ISO-10545-12	Stands the test
Chemical restistance Domestic and swimming pool product Acids and alkalis of low concentration	UNE-EN-ISO-10545-13	Class A Min class LB
Resitance to stains	UNE-EN-ISO-10545-14	Min class 4
Resitance to fire	Decision 96/603/CE	

