

Collection: RE-BEL
Color: Petrol
Top finish: Mat
Size: 60 x 60cm (23,62x26,62 in)
Thickness: 9,5 mm
Material Type: Porcelain - single firing - dry pressed ceramic tile



TECHNICAL DATA

	Standard test	Value required by UNE-EN-14411	Avarage value
Dimensional features:	UNE-EN-ISO-10545-2	Conforms to the requisites	
Water absorption:	UNE-EN-ISO-10545-3	E<0.5%	Eb 0.1%
Bending strenght	UNE-EN-ISO-10545-4	>35Nw/mm ² >1300Nw	44 Nw/mm ² 1923 Nw
Modulus of rupture			
Breaking strenght			
Resistance to surface abrasion	UNE-EN-ISO-10545-7		PEI IV
Linear thermal expansion	UNE-EN-ISO-10545-8	<9*10 ⁻⁶ /°C	Declared value
Thermal shock restistance	UNE-EN-ISO-10545-9	Required	Stands the test
Cracking resistance	UNE-EN-ISO-10545-11	Required	Stands the test
Frost restistance	UNE-EN-ISO-10545-12	Required	Stands the test
Chemical restistance	UNE-EN-ISO-10545-13		Class A HA - LA
Domestic and swimming pool products			
Acids and alkalis of low conentration			
Resitance to stains	UNE-EN-ISO10545-14	Min class 4	5
Friction coeficient			PTV 36 R10 Not apply
Pendulum	UNE-ENV-12633		
Ramp	DIN51130		
DCOF	ANSI A137.1	Declared value	
Resistance to fire	Decision 96/603/CE		Not apply

CE MARKING



CE Declaration of performance:
N° 001VV2019