

Collection: RE-BEL
 Color: Vert
 Top finish: Mat - R10
 Size: 60 x 60cm & 100x100
 Thickness: 9,5 mm & 10mm
 Material Type: Porcelain - single firing - dry pressed ceramic tile



V-Shade : 1

TECHNICAL DATA

	Standard test	Value required by UNE-EN-14411	Average value
Dimensional features:	UNE-EN-ISO-10545-2	Conforms to the requisites	
Water absorption:	UNE-EN-ISO-10545-3	E<0.5%	Eb 0.1%
Bending strenght Modulus of rupture Breaking strenght	UNE-EN-ISO-10545-4	>35Nw/mm ² >1300Nw	44 Nw/mm ² 1923 Nw
Resistance to surface abrasion	UNE-EN-ISO-10545-7		PEI IV
Linear thermal expansion	UNE-EN-ISO-10545-8	<9*10 ⁻⁶ /°C	Declared value
Thermal shock restistance	UNE-EN-ISO-10545-9	Required	Stands the test
Cracking resistance	UNE-EN-ISO-10545-11	Required	Stands the test
Frost restistance	UNE-EN-ISO-10545-12	Required	Stands the test
Chemical restistance Domestic and swimming pool products Acids and alkalis of low conentration	UNE-EN-ISO-10545-13		Class A HA - LA
Resitance to stains	UNE-EN-ISO10545-14	Min class 4	5
Friction coeficient Pendulum Ramp DCOF	UNE-ENV-12633 DIN51130 ANSI A137.1		PTV 45 wet - class 2 Class B - R10 Declared value 0.67
Resistance to fire	Decision 96/603/CE		Not apply

CE MARKING



CE Declaration of performance:
 N° 001VV2019